
DATASHEET

Single-SLED Optical Spectral Engine G1: 14-Pin Butterfly Package, 1 SLED: 1680nm, PM Fiber, High Degree of Polarization, Spectral Coverage: 1657nm-1703nm, FWHM: 45nm, CW: 1680nm, Fiber Output Power >13mW.

Part# ASM002025



This document is the property of DAYY Photonics, and contains proprietary information. DAYY Photonics reserves the right to make product design or specification changes without notice.
DAYY Photonics, 5150 Tacoma Dr, Houston, TX, USA 77041
sales@dayyphotonics.com, +1 (346) 263-3032, www.dayyphotonics.com

A. PRODUCT DESCRIPTION

This solution is a superluminescent diode (SLED) that comes in a 14-pin butterfly package, and operates within the near-infrared region (NIR). It is a compact package that provides an integrated optical interface and one of the highest power densities within the SLED technology industry.


This package offers spectral coverage from 1657nm to 1703nm, with minimum 10mW of optical power. The temperature of the device is regulated by an integrated thermoelectric cooler (TEC). This light source is robust and easy-to-use, making it an appropriate fit for many different types of manufactured assemblies requiring light power, including the applications below:

B. KEY FEATURES

- SLED can be run from 0 – 100% of maximum rating
- Output power: >13mW
- Bandwidth FWHM: 45nm
- Light output: FC/APC Connector (Optional: FC/PC or SMA)
- SLED comes with a built-in independent monitor photodiode and one thermoelectric cooler (TEC)

C. APPLICATIONS

- Optical Component Testing
- Telecom Test Equipment
- Medical Optical Coherence Tomography
- Industrial Optical Coherence Tomography
- Metrology
- Fiber Optic Gyroscopes
- Biomedical Imaging Systems
- Optical Sensing
- White Light Interferometry & Chromatic Dispersion
- Research and Development









This document is the property of DAYY Photonics, and contains proprietary information. DAYY Photonics reserves the right to make product design or specification changes without notice.

DAYY Photonics, 5150 Tacoma Dr, Houston, TX, USA 77041
sales@dayyphotonics.com, +1 (346) 263-3032, www.dayyphotonics.com

D. ABSOLUTE MAXIMUM RATINGS (see note 1)

Parameter	Symbol	Condition	Min.	Max.	Unit
Reverse Voltage	V_R	CW	-	2	V
Forward Voltage	V_F	CW T_{OP} = 25˚C T_{TEC} = 21˚C	-	3.0	V
BTF Package Temperature (see note 2)	T_{BTF}	-	-40	80	˚C
SLED Operating Temperature	T_{SLED}	I_{OP}	0	70	˚C
TEC Current	I_{TEC}	-	-	3	A
TEC Voltage	V_{TEC}	-	-	4	V
TEC Temperature (see note 3)	T_{TEC}	-	0	50	˚C
Storage Temperature (see note 4)	T_{stg}	No condensation, Unbiased	-40	85	˚C
Storage Humidity (see note 4)	RH_{stg}	-	5	85	%RH
Electro Static Discharge (ESD)	V_{ESD}	Human Body Model	-	500	V
Lead Soldering Temperature	T_{Solder}	-	-	280	˚C
Lead Soldering Time	t_{Solder}	-	-	10	s

Notes:

1. *Please note that exceeding the Absolute Maximum Ratings above may cause device failure. The manufacturer does not bear responsibility for laser power damage that is attributed to electrostatic discharge, excessive current levels, and current spikes (transients).*

   Any attempts to increase the laser drive current above the pre-set limits or recommended specification limits, can damage the device, and nullify the warranty period. It should be emphasized that the current limit set points cannot be exceeded.

2. *For optimum performance of the SLED, the SLED must be operated within the specified temperature ranges. The SLED has an internal thermoelectric cooler (TEC) but it's always required to mount the butterfly package on an appropriate heatsink, capable of dissipating up to 7W.*

3. T_{TEC} *is monitored by internal thermistor with external readout.*

4. *Storage temperature and relative humidity should be chosen so the dew point of the humid air around the package is below the storage temperature of the package, to avoid condensation on the package.*

This document is the property of DAYY Photonics, and contains proprietary information. DAYY Photonics reserves the right to make product design or specification changes without notice.
DAYY Photonics, 5150 Tacoma Dr, Houston, TX, USA 77041
sales@dayyphotonics.com, +1 (346) 263-3032, www.dayyphotonics.com

E. OPTICAL AND ELECTRICAL SPECIFICATIONS (see note 5)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Center Wavelength (see note 6)	CWL	T_{OP} = 25˚C T_{TEC} = 21˚C I_{OP}	1670	1680	1690	nm
Operating Current	I_{OP}	T_{OP} = 25˚C T_{TEC} = 21˚C I_{OP}	-	400	450	mA
Forward Voltage	V_F	T_{OP} = 25˚C T_{TEC} = 21˚C I_{OP}	-	-	2	V
PM Fiber Coupled Power	P	T_{OP} = 25˚C T_{TEC} = 21˚C I_{OP}	13	-	-	mW
Bandwidth FWHM (see note 7)	B_{FWHM}	T_{OP} = 25˚C T_{TEC} = 21˚C I_{OP}	45	-	-	nm
Spectral Coverage	SC	T_{OP} = 25˚C T_{TEC} = 21˚C I_{OP}	-	1657 – 1703	-	nm
Spectrum Ripple (see note 8)	R	T_{OP} = 25˚C T_{TEC} = 21˚C I_{OP}	<0.15	<0.30	<0.45	dB
Polarization Extinction Ratio (see note 9)	PER	T_{OP} = 25˚C T_{TEC} = 21˚C I_{OP}	10	-	-	dB
Thermistor Resistance TEC	R_{THTEC}	T_{OP} = 25˚C T_{TEC} = 21˚C	9.5	10.0	10.5	kΩ
Monitor Photodiode Current	M_{CURR}	T_{OP} = 25˚C T_{TEC} = 21˚C	-	-	25	mA
Power Dissipation (see note 10)	P_{DISS}	I_{OP}	-	4	-	W
TEC Voltage	V_{TEC}	-	-	-	3.5	V
TEC Current	I_{TEC}	-	-	-	2.5	A

Notes:

5. *There may be differences in typical values of output power, power stability, wavelength and bandwidth, due to coupling efficiency. These values are references and there is no guarantee that each particular SLED module will have EXACTLY the typical values shown on the previous chart. The specification lists the operating temperature for the electrical/optical characteristics, which is the temperature of the SLED during the time that the specifications were measured. Variation in temperature beyond what is specified can have a significant effect on the optical characteristics, like changes in wavelength or drop in output power.*
6. *Center Wavelength is defined as the center point of the 3dB bandwidth of the SLED.*
7. *SLED FWHM is defined as the -3dB bandwidth from the center wavelength.*
8. *Resolution of 0.1nm.*
9. *Polarization Extinction Ration is defined as the ratio of optical powers of perpendicular polarizations, expressed in decibels (dB).*
10. *Power dissipation when SLED is on and $|T_{BTF} - T_{TEC}|$ is 40°C.*

This document is the property of DAYY Photonics, and contains proprietary information. DAYY Photonics reserves the right to make product design or specification changes without notice.
DAYY Photonics, 5150 Tacoma Dr, Houston, TX, USA 77041
sales@dayyphotonics.com, +1 (346) 263-3032, www.dayyphotonics.com

F. PLOTS – Test performed at T_{OP}=25°C and T_{TEC}=21°C

FIG. 1: BTF PACKAGE SPECTRUM




FIG. 2: BTF PACKAGE OUTPUT POWER VS CURRENT




FIG. 3: BTF PACKAGE FORWARD VOLTAGE VS CURRENT






FIG. 4: THERMISTOR R_{THTEC} RESISTANCE VS TEMP.



G. PIN OUT


External Pin Assignment			
1	TEC +	**8**	NC
2	THERMISTOR	**9**	NC
3	M-PD ANODE (+)	**10**	SLEAD ANODE (+)
4	M-PD CATHODE (-)	**11**	SLED CATHODE (-)
5	THERMISTOR	**12**	NC
6	NC	**13**	CASE GND
7	NC	**14**	TEC -



This document is the property of DAYY Photonics, and contains proprietary information. DAYY Photonics reserves the right to make product design or specification changes without notice.

DAYY Photonics, 5150 Tacoma Dr, Houston, TX, USA 77041
sales@dayyphotonics.com, +1 (346) 263-3032, www.dayyphotonics.com

H. MECHANICAL DIAGRAM



Part	Description
Package type	14-pin Butterfly
Fiber:	PM1550-XP
Core Diameter	8µm
Cladding Diameter	125µm
Coating Diameter	245µm
Jacket	900µm loose tube
Fiber pigtail length	1m
Fiber bending radius	>40mm
Connector	Standard: FC/APC
Dimensions	See figure

This document is the property of DAYY Photonics, and contains proprietary information. DAYY Photonics reserves the right to make product design or specification changes without notice.
DAYY Photonics, 5150 Tacoma Dr, Houston, TX, USA 77041
sales@dayyphotonics.com, +1 (346) 263-3032, www.dayyphotonics.com

I. MOUNTING RECOMMENDATIONS:

The SLED can be mounted on a flat cooling surface without having to risk forming the pins. Mounting surface should be flat, with no physical obstructions underneath to cause any discontinuity in the surface flatness. If a heatsink is used, the base of the butterfly package will rest on the surface of a heatsink in order to cool the internal TEC.

Maximum torque to avoid damage to the device is 13 lb.in. /1.5 Nm. Minimum torque is 9 lb.in/1.1 nm. Do not use self-tapping screws. This light source should be mounted so that mechanical vibrations cannot cause short circuits between leads. AZIMUTH 7 pin, 0.100" pitch Sockets are recommended. The 14 pins will rest on a pair of spring-loaded sockets and be squeezed between the contacts and a plastic clamp.

J. SAFETY

All statements regarding safety of operation and technical data will only apply when the unit is operated correctly.

This SLED is a Class 1M laser product. It is safe for all conditions of use except when passed through magnifying optics such as microscopes and telescopes. It produces a beam that is divergent. If light is re-focused use protective eye wear.

This document is the property of DAYY Photonics, and contains proprietary information. DAYY Photonics reserves the right to make product design or specification changes without notice.
DAYY Photonics, 5150 Tacoma Dr, Houston, TX, USA 77041
sales@dayyphotonics.com, +1 (346) 263-3032, www.dayyphotonics.com